

## POLYAMIDE PA6 V-0 CABLE GLANDS, METRIC / PG

Material Polyamide PA6 V-0  
 Connecting thread Metric (EN 60423), PG  
 Temperature range -30 °C up to +100 °C  
 Protection grade IP68 – 5 bar  
 Test standard EN 62444 / UL 514B, UL-approved  
 Standard colors Light grey (RAL 7035), black (RAL 9005)



Part.nr Grey	Part.nr Black	Thread	Cabel Ø mm	Key width mm	Thread length mm	Colour	Colour
177.120365.00	177.120365.01	M 12x1.5	3-6.5	15	8	Gray (RAL 7035)	Black (RAL 9005)
177.174510.00	177.174510.01	M 16x1.5	4.5-10	19	8	Gray (RAL 7035)	Black (RAL 9005)
177.200612.00	177.200612.01	M 20x1.5	6-12	24	9	Gray (RAL 7035)	Black (RAL 9005)
177.201014.00E	177.201014.01E	M 20x1.5	10-14	27	11	Gray (RAL 7035)	Black (RAL 9005)
177.250917.00	177.250917.01	M 25x1.5	9-17	30	10	Gray (RAL 7035)	Black (RAL 9005)
177.321825.00	177.321825.01	M 32x1.5	18-25	42	10	Gray (RAL 7035)	Black (RAL 9005)
177.321220.00R	177.321220.01R	M 32x1.5	12-20	42	10	Gray (RAL 7035)	Black (RAL 9005)
177.402232.00	177.402232.01	M 40x1.5	22-32	53	13	Gray (RAL 7035)	Black (RAL 9005)
177.401928.00N	177.401928.01N	M 40x1.5	19-28	46	10	Gray (RAL 7035)	Black (RAL 9005)
177.503038.00	177.503038.01	M 50x1.5	30-38	60	13	Gray (RAL 7035)	Black (RAL 9005)
177.502735.00N	177.502735.01N	M 50x1.5	27-35	55	12	Gray (RAL 7035)	Black (RAL 9005)
177.633242.00	177.633242.01	M 63x1.5	32-42	68	14	Gray (RAL 7035)	Black (RAL 9005)
Part.nr Grey	Part.nr Black	Thread	Cabel Ø mm	Key width mm	Thread length mm	Colour	Colour
177.120365.00L	177.120365.01L	M 12x1.5	3-6.5	15	15	Gray (RAL 7035)	Black (RAL 9005)
177.174510.00L	177.174510.01L	M 16x1.5	4.5-10	19	15	Gray (RAL 7035)	Black (RAL 9005)
177.201014.00L	177.201014.01L	M 20x1.5	6-12	24	15	Gray (RAL 7035)	Black (RAL 9005)
177.250917.00L	177.250917.01L	M 25x1.5	9-17	30	15	Gray (RAL 7035)	Black (RAL 9005)
177.321825.00L	177.321825.01L	M 32x1.5	18-25	42	15	Gray (RAL 7035)	Black (RAL 9005)
177.402232.00L	177.402232.01L	M 40x1.5	22-32	53	18	Gray (RAL 7035)	Black (RAL 9005)
177.401928.00LN	177.401928.01LN	M 40x1.5	19-28	46	18	Gray (RAL 7035)	Black (RAL 9005)
177.503038.00L	177.503038.01L	M 50x1.5	30-38	60	18	Gray (RAL 7035)	Black (RAL 9005)
177.502735.00LN	177.502735.01LN	M 50x1.5	27-35	55	18	Gray (RAL 7035)	Black (RAL 9005)
177.633242.00L	177.633242.01L	M 63x1.5	32-42	68	18	Gray (RAL 7035)	Black (RAL 9005)
Part.nr Grey	Part.nr Black	Thread	Cabel Ø mm	Key width mm	Thread length mm	Colour	Colour
177.070365.00	177.070365.01	Pg 7	3-6.5	15	8	Gray (RAL 7035)	Black (RAL 9005)
177.090408.00	177.090408.01	Pg 9	4-8	19	8	Gray (RAL 7035)	Black (RAL 9005)
177.114510.00	177.114510.01	Pg 11	4.5-10	22	8	Gray (RAL 7035)	Black (RAL 9005)
177.130612.00	177.130612.01	Pg 13	6-12	24	9	Gray (RAL 7035)	Black (RAL 9005)
177.161014.00	177.161014.01	Pg 16	10-14	27	11	Gray (RAL 7035)	Black (RAL 9005)
177.211318.00	177.211318.01	Pg 21	13-18	33	11	Gray (RAL 7035)	Black (RAL 9005)
177.291825.00	177.291825.01	Pg 29	18-25	42	11	Gray (RAL 7035)	Black (RAL 9005)
177.362232.00	177.362232.01	Pg 36	22-32	53	13	Gray (RAL 7035)	Black (RAL 9005)
177.423038.00	177.423038.01	Pg 42	30-38	60	13	Gray (RAL 7035)	Black (RAL 9005)
177.483444.00	177.483444.01	Pg 48	32-44	65	14	Gray (RAL 7035)	Black (RAL 9005)