

## Non-metallic conduit systems

### Type FL/A, FL/C90 & FL/90 - Adaptalok

#### Type FL/A - Adaptalok

Straight panel mounting swivel flange / Materials: Polyamide (nylon) 66 / Colour: Black (BL), Grey (GR)



Part no.	Nominal conduit size (mm)
AL16/FL/A	16
AL21/FL/A	21
AL28/FL/A	28
AL54/FL/A	54

With integral face seal  
To order quote part number & body colour, e.g. AL16/FL/A/BL

#### Approvals



#### IP rating

#### Appropriate conduit

For use with: Type PA / CP / PR / PF

IP66	Yes
IP67	Yes + ALS Seal
IP68	Yes + ALS Seal
IP69	Yes + ALS Seal

#### Temperature range

Static applications: -50°C to +120°C

Moving applications: -45°C to +120°C

#### Fitting characteristics



#### Type FL/C90 - Adaptalok

90° Elbow body - Panel mount swivel flange / Materials: Polyamide (nylon) 66 / Colour: Black (BL), Grey (GR)



Part no.	Nominal conduit size (mm)
AL13/FL/C90	13
AL16/FL/C90	16
AL21/FL/C90	21
AL28/FL/C90	28

For panel mounting via 2 hole fixing & integral face seal  
To order quote part number & body colour, e.g. AL13/FL/C90/BL

#### Type FL/90 - Adaptalok

90° Elbow body - Panel mount flange / Materials: Polyamide (nylon) 66 / Colour: Black (BL), Grey (GR)



Part no.	Nominal conduit size (mm)
AL34/FL/90	34
AL42/FL/90	42
AL54/FL/90	54

For panel mounting via 4 hole fixing & integral face seal  
To order quote part number & body colour, e.g. AL34/FL/C90/BL

#### Approvals



#### IP rating

#### Appropriate conduit

For use with: Type PA / CP / PR / PF

IP66	Yes
IP67	Yes + ALS Seal
IP68	Yes + ALS Seal
IP69	Yes + ALS Seal

#### Temperature range

Static applications: -50°C to +120°C

Moving applications: -45°C to +120°C

#### Fitting characteristics (FLC/90 ONLY)

