



AWAS

Heavy-wall heat shrink tubing / heat shrinkable cable repair sleeve with glue

Features:

- Heat shrinkable wrap around sleeve • Good environmental protection
- Good electrical and mechanical performance • Ideal for low voltage applications
- UV and weather resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -40 °C to +110 °C • Longitudinal change: 0 ± 10% max.

Order information:

- Color: black



The sleeves are lined with hot-melt adhesive to ensure protection against moisture or water penetration.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Standard lengths in mm
AWAS 36/10	38,0	9,0	2,4	500, 750, 1000, 1500
AWAS 55/13	57,0	13,0	2,5	500, 750, 1000, 1500
AWAS 85/20	85,0	20,0	3,0	500, 750, 1000, 1500
AWAS 108/27	110,0	27,0	3,0	500, 750, 1000, 1500
AWAS 136/30	138,0	30,0	3,2	500, 750, 1000, 1500
AWAS 180/50	183,0	50,0	3,2	500, 750, 1000, 1500

Other wrap around sleeves are also available on special request

- AWAS-S: fiber glass reinforcing layer with aluminum moisture vapour barrier layer.
- AWAS-G: Thermo-chromic Paint.
- AWAS-M: Mastic Inner Layer.