

STANDARD

Features:

Material	: Polyamide 6.6
Color	: Transparent / black (UV resistant) : Other colors available on request
Temperature range	: -40 °C up to +85 °C
Flammability	: UL 94 V2 (V0 available)
Certification	: UL, Lloyd's, GL 59425-08HH



For transparent/natural tie's change last digit to _9

Typenr.	Length (mm)	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Packing (pcs)	Pcs per carton	Normal stock item
						100 pcs / pack	X = yes
400008002400	80	2,4	15	8,0	100	70.000	-
400010002500	100	2,5	22	8,1	100	55.000	X
400012002500	120	2,5	30	8,1	100	45.000	-
400014002500	140	2,5	33	8,1	100	45.000	X
400016002500	160	2,5	40	8,1	100	40.000	-
400020002500	200	2,5	53	8,1	100	30.000	X
400014003600	140	3,6	33	18,2	100	30.000	-
400015003600	150	3,6	35	18,2	100	30.000	X
400020003600	200	3,6	53	18,2	100	20.000	X
400030003600	300	3,6	76	18,2	100	17.000	-
400037003600	370	3,6	102	18,2	100	12.000	X
400012004800	120	4,8	24	22,2	100	20.000	-
400016004800	160	4,8	38	22,2	100	16.000	-
400019004800	190	4,8	46	22,2	100	16.000	-
400020004800	200	4,8	50	22,2	100	16.000	X
400025004800	250	4,8	60	22,2	100	12.000	-
400028004800	280	4,8	70	22,2	100	11.000	-
400030004800	300	4,8	76	22,2	100	11.000	X
400037004800	370	4,8	102	22,2	100	9.000	X
400039004800	390	4,8	105	22,2	100	8.500	-
400043004800	430	4,8	110	22,2	100	7.500	X
400053004800	530	4,8	140	22,2	100	5.600	-

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. BOXCO shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.

STANDARD

Material	: Polyamide 6.6
Color	: Transparent / black (UV resistant) : Other colors available on request
Temperature range	: -40 °C up to +85 °C
Flammability	: UL 94 V2 (V0 available)
Certification	: UL, Lloyd's, GL 59425-08HH



For transparent/natural tie's change last digit to _9

Typenr.	Length (mm)	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Packing (pcs)	Normal stock item	
						Pcs per carton	100 pcs / pack
400015007600	150	7,6	33	54,4	100	8.000	-
400020007600	200	7,6	50	54,4	100	7.000	-
400025007600	250	7,6	65	54,4	100	6.000	-
400030007600	300	7,6	76	54,4	100	5.000	-
400037007600	370	7,6	102	54,4	100	4.000	X
400045007600	450	7,6	132	54,4	100	2.500	X
400053007600	530	7,6	140	54,4	100	2.000	X
400061507600	615	7,6	176	54,4	100	2.000	-
400075007600	750	7,6	218	54,4	100	2.000	X
400043009000	430	9,0	110	79,4	100	2.500	X
400053009000	530	9,0	140	79,4	100	2.000	X
400061009000	610	9,0	187	79,4	100	2.000	-
400071009000	710	9,0	190	79,4	100	2.000	-
400078009000	780	9,0	228	79,4	100	2.000	X
400083009000	830	9,0	239	79,4	100	1.500	-
400092009000	920	9,0	263	79,4	100	1.200	-
400102009000	1020	9,0	295	79,4	100	1.000	-
400122009000	1220	9,0	365	79,4	100	1.000	-
400153009000	1530	9,0	460	79,4	100	500	-
400023001300	230	13,0	50	114,0	100	3.000	-
400048001300	480	13,0	120	114,0	100	1.500	-
400058001300	580	13,0	152	114,0	100	1.200	X
400073001300	730	13,0	204	114,0	100	1.000	-
400088001300	880	13,0	248	114,0	100	600	-
400103001300	1030	13,0	295	114,0	100	600	-

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. BOXCO shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.