

PREMIUM 85 CW

An 8.5 mil (0,21mm) all weather, professional grade, pressure sensitive vinyl tape that provides heavier thickness for added mechanical and electrical protection. Cold and weather resistant. Flame retardant. Can be used as primary insulation for splices at not more than 600 Volts. Excellent protective jacket over all types of splices. UL 510, ASTM-D-3005, MIL-T24391C. Lead-free.

PREMIUM 37 Color Coding

A 7 mil (0,18mm) all weather, professional grade, pressure sensitive vinyl tape that is available in nine colors for color coding and insulating. Cold and weather resistant. Flame Retardant. Use Premium 37 for quick identification of electrical circuits, containers, and conduit systems, as well as primary insulation for splices at not more than 600 volts. UL 510, ASTM-D-3005, HH-595C. Lead-free.

VINYL ELECTRICAL TAPES



PREMIUM 85 CW

Cat.	Color	Dimensions	Packaging	Weight
4240	black	3/4" x .0085" x 66'	19mm x 0,21mm x 20m	100/case PC 28 lbs 13 kg
4241	black	2" x .0085" x 20'	50mm x 0,21mm x 6m	108/case PC 23 lbs 10 kg
4274	black	2" x .0085" x 108'	50mm x 0,21mm x 33m	40/case PC 35 lbs 16 kg
4252	black	1 1/2" x .0085" x 66'	38mm x 0,21mm x 20m	100/case C 38 lbs 17 kg
4273	black	1 1/2" x .0085" x 108'	38mm x 0,21mm x 33m	50/case C 38 lbs 17 kg
4311	black	2" x .0085" x 66'	50mm x 0,21mm x 20m	40/case C 28 lbs 13 kg
4243	black	3/4" x .0085" x 66'	19mm x 0,21mm x 20m	100/case C 23 lbs 10 kg

PREMIUM 37 Color Coding (Plastic Can)

Dimensions	Packaging	Weight
3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PC	5 lbs 2 kg
Cat.&Color	3702 green 3703 yellow 3704 red 3705 blue 3706 white 3707 brown 3708 orange 3709 grey 3711 violet	

PREMIUM 37 Color Coding (Cello+Label)

Dimensions	Packaging	Weight
3/4" x .007" x 66' 19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
Cat.&Color	8756 green 8754 yellow 8751 red 8753 blue 8752 white 8757 brown 8759 orange 8755 grey 8758 violet	