



## ABBM

### Halogen free flexible busbar insulation tubing

#### Features:

- ABBM = medium-wall tubing • Medium-wall flexible busbar insulation tubing
- Modified Polyolefin • Excellent electrical properties and creeping resistance
- Halogen free • UV and weather resistant • Up to 36 kV

#### Approvals:

- Meets: RoHS

#### Application:

- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

#### Order information:

- Color: red



Provides insulation enhancement  
and protection against  
flashover and accidentally  
induced discharge

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Reel / Meter & Standard length in mm
ABBM 15/6	15,0	6,0	2,5	30 meter
ABBM 25/10	25,0	10,0	2,9	30 meter
ABBM 30/12	30,0	12,0	2,9	30 meter
ABBM 40/16	40,0	16,0	2,9	30 meter
ABBM 50/20	50,0	20,0	2,9	15 meter
ABBM 65/25	65,0	25,0	2,9	15 meter
ABBM 75/30	75,0	30,0	2,9	15 meter
ABBM 100/40	100,0	40,0	2,9	15 meter
ABBM 120/50	120,0	50,0	2,9	15 meter

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. BOXCO shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.